

Hose
A

Fittings
B

Parkrimp
Equipment
C

Accessories
D

Technical
E

Karrykrimp



Features

- Portable, compact rugged design
- Numerous power unit options available
- Pivoting pusher design for easy die change out
- For use with 25, 26, 43, 81, and HY Series fittings

Specifications

- Dimensions: 15" wide, 12" deep, 27" high
- Weight: 54 lbs (without power unit)
- Rating: 30 ton force @ 10,000 psi maximum
- Full Cycle Time: 30 seconds with electric pump
- Reference page C-20 for information on available power units

Standard Equipment

Part Number				Description	Individual Part Number
82C-001	82C-002	82C-061	82C-080		
●	●	●	●	Karrykrimp portable crimper (base unit)	82C-080
●	●	●		2 piece stand	832021
●				Hand pump	82C-0HP
●	●	●		Connection hose with quick coupling	82C-00L
●	●	●		Silver die ring	82C-R01
●	●	●		Black die ring	82C-R02
●	●			43 Series dies (sizes 1/4", 3/8", 1/2", 3/4" and 1")	80C-Axx

Parkrimp 1



Features

- Compact bench mount design
- Engineered for optimal durability
- All in one crimper and power unit design
- For use with 25, 26, 43, 81, and HY Series fittings

Specifications

- Dimensions: 26" wide, 20" deep, 25" high
- Weight: 275 lbs (with power unit)
- Rating: 30 ton force @ 3,000 psi maximum
- Full Cycle Time: 20 seconds
- Hydraulic Fluid: AW32 oil
- **Note:** Includes a 115/230 volt, 1 phase, 60 hertz power unit wired for 115V. This unit comes with a 20 AMP male plug and must be run on a dedicated 20 AMP circuit.

Standard Equipment

Part Number			Description	Individual Part Number
80C-101	80C-061	80C-181		
●	●	●	Parkrimp 1 crimper with 115/230 volt, 1 phase, 60 Hz power unit wired for 115V	80C-181
●	●		Silver die ring	80C-R01
●	●		Black die ring	80C-R02
●			43 Series dies (sizes 1/4", 3/8", 1/2", 3/4" and 1")	80C-Axx

Note:

- For crimp instructions, see pages C-16 and C-17.
- Hose assemblies must be inspected for cleanliness and free of all foreign particles.
- Parker Hannifin will not accept responsibility for the operation of, or provide warranty coverage for, a crimper that is operated by a power unit other than equipment supplied by Parker Hannifin for the express purpose of operating the crimper.